

US008181561B2

# (12) United States Patent

# Riggs et al.

#### (54) EXPLOSIVE DECOMPRESSION PROPULSION SYSTEM

- (75) Inventors: Jeffrey L. Riggs, Pittsboro, NC (US);
  Vladislav Oleynik, Pittsboro, NC (US);
  Valery Borovikov, Saint Petersburg (RU); Gennadiy Albul, Pittsboro, NC (US)
- (73) Assignee: Causwave, Inc., Pittsboro, NC (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 70 days.
- (21) Appl. No.: 12/476,555
- (22) Filed: Jun. 2, 2009 (Under 37 CFR 1.47)

#### (65) **Prior Publication Data**

US 2012/0097144 A1 Apr. 26, 2012

# **Related U.S. Application Data**

- (60) Provisional application No. 61/130,547, filed on Jun. 2, 2008.
- (51) Int. Cl.
- *F41F 3/04* (2006.01)
- (52) U.S. Cl. ...... 89/1.817; 89/1.8; 89/1.816; 102/370

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

421,306	А	*	2/1890	Reynolds	. 124/75
1,985,184	Α	¥	12/1934	Methlin	114/238
2,753,801	Α	*	7/1956	Cumming	102/381
2,879,955	Α	*	3/1959	Von Zborowski	244/3.22

# (10) Patent No.: US 8,181,561 B2

# (45) **Date of Patent:** May 22, 2012

2,927,398 2,960,033 3,031,932 3,049,832 3,082,666 3,135,163 3,158,100	A A A A A A A	* * * * * * *	3/1960 11/1960 5/1962 8/1962 3/1963 6/1964 11/1964	Kaye et al.      446/212        Jackson      102/377        Fite, Jr.      89/1.806        Joffe      446/212        Fitzpatrick et al.      89/1.806        Mechlin, Jr. et al.      89/1.81        Finley      102/377
3,158,100 3,167,016	A A	*	11/1964 1/1965	Finley 102/377 Czerwinski et al
,10.,010	•••		1, 19 00	

(Continued)

# FOREIGN PATENT DOCUMENTS

0559547 A1 9/1993

(Continued)

#### OTHER PUBLICATIONS

V. P. Korobeinikov (Propagation of shock and detonation waves in dust-laden gases, Journal: Fluid Dynamics, Publisher: MAIK Nauka/ Interperiodica distributed exclusively by Springer Science+Business Media LLC., ISSN: 0015-4628 (Print) 1573-8507 (Online); Issue vol. 19, No. 6 / Nov. 1984; pp. 938-943).\*

(Continued)

Primary Examiner — Benjamin P Lee

EP

Assistant Examiner — Joshua Freeman

(74) *Attorney, Agent, or Firm*—R. Brian Drozd; Nelson Mullins Riley & Scarborough LLP

#### (57) **ABSTRACT**

A projectile propulsion system includes a launch tube, multiphase material, and a membrane. The launch tube has an interior cavity, the multiphase material disposed therein. The launch tube also has an opening to receive the multiphase material. The membrane seals the opening while the multiphase material is disposed in the interior cavity of the launch tube so as to allow the launch tube to be pressurized. When the membrane is broken, a supersonic wave thrusts the contents of the interior cavity, such as a projectile, outwards with a high velocity and force.

#### 13 Claims, 15 Drawing Sheets



#### U.S. PATENT DOCUMENTS

3,167,061	A *	1/1965	Murray	124/60
3,198,073	A *	8/1965	Van Tine et al	89/1.816
3,252,281	A *	5/1966	Everett et al	60/227
3.313.207	A *	4/1967	Biehl et al	89/1.814
3,323,531	A *	6/1967	Spellman	137/68.19
3,353,823	A *	11/1967	Sobel	472/54
3,369,455	A *	2/1968	Jones	89/1.818
3,397,638	A *	8/1968	Gould	102/377
3,422,808	A *	1/1969	Veinberg et al.	124/61 116/127 A
3,428,022	Δ*	2/1909	Black et al	102/374
3.620.123	A *	11/1971	Davidsson et al.	9/1.8
3,633,560	A *	1/1972	DeFreitas	124/56
3,715,983	A *	2/1973	Rosinski	241/1
3,754,726	A *	8/1973	Rusbach	244/3.28
3,842,598	A *	10/19/4	Forsten	60/259
4 038 115	A *	7/1977	Dehm	140/19 8
4.185.538	Â*	1/1980	Barakauskas	89/1.81
4,333,402	A *	6/1982	Landstrom et al	102/505
4,373,420	A *	2/1983	Piesik	89/1.812
4,389,938	A *	6/1983	Sigrist	102/337
4,444,085	A *	4/1984	Dragonuk	89/1.51
4,455,917	A · A *	0/1984	SHOOK	80/1.817
4.682.559	A *	7/1987	Schnitzer et al.	114/295
4,784,035	A *	11/1988	Fishfader et al.	89/1.34
H684	Н *	10/1989	Arszman et al	102/377
4,932,306	A *	6/1990	Rom	
5,015,211	A *	5/1991	Reveen	446/475
5,063,826	A *	1/1991	Bulman	89/8 דבובד
5,081,802	Α · Δ *	3/1992	Hertzberg et al	
5.099.645	A *	3/1992	Schuler et al.	60/219
5,149,290	A *	9/1992	Reveen	446/475
5,170,005	A *	12/1992	Mabry et al	89/1.81
5,174,384	A *	12/1992	Herman	169/70
5,355,764	A *	10/1994	Marinos et al	
5,440,995	A *	8/1995	Osoisky	102/374
5.584.736	A *	12/1990	Salvemini	441/85
5,623,113	Â*	4/1997	Valembois	
5,652,405	A *	7/1997	Rakov	
5,833,393	A *	11/1998	Carnahan et al	405/79
5,847,307	A *	12/1998	Kennedy et al	89/1.817
5,864,517	A *	6/1000	Pakov	307/145
5,927,329	A *	7/1999	Yie	137/624.13
5,964,985	A *	10/1999	Wootten	201/40
5,993,921	A *	11/1999	Hunn	. 428/34.4
6,124,563	A *	9/2000	Witherspoon et al	219/121.47
6,138,766	A *	10/2000	Finnerty et al.	169/14
6,142,055	A * B1	5/2001	Borgwarth et al	89/1.81/
6.257.340	B1*	7/2001	Vician	169/5
6,276,354	BI*	8/2001	Dillon	124/74
6,352,030	B1 *	3/2002	Doll et al.	102/291
6,427,574	B1 *	8/2002	Callahan	89/1.81
6,526,860	B2 *	3/2003	Facciano et al.	89/1.801
6,550,074	BI *	4/2005	Allenbaugh et al.	4/200.11
6 854 400	D1*	6/2004	Griffin	20/1 217
(1, 0, 94, 407)	B1 * B1 *	6/2004 2/2005	Griffin	89/1.817
6,979,021	B1 * B1 * B2 *	6/2004 2/2005 12/2005	Griffin	89/1.817 114/238 280/737
6,979,021 7,182,014	B1 * B1 * B2 * B2 *	6/2004 2/2005 12/2005 2/2007	Griffin	89/1.817 114/238 280/737 89/16
6,979,021 7,182,014 7,267,230	B1 * B1 * B2 * B2 * B1 *	6/2004 2/2005 12/2005 2/2007 9/2007	Griffin Galliano Young et al. Smith Smith	89/1.817 114/238 280/737 89/16 209/139.1
6,979,021 7,182,014 7,267,230 7,313,881	B1* B1* B2* B2* B1* B1* B1*	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008	Griffin Galliano Young et al. Smith Smith Gieseke et al.	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14
6,979,021 7,182,014 7,267,230 7,313,881 7,317,662	B1* B1* B2* B2* B1* B1* B2* B2* B2* B2*	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 1/2008 2/2009	Griffin	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 89/1 818
6,934,409 6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617 818	B1* B1* B2* B2* B1* B1* B2* B2* B2* B1*	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 1/2008 2/2009 11/2009	Griffin Galliano Young et al. Smith Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al.	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 89/1.818 124/64
6,334,405 6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617,818 7,637,203	B1* B1* B2* B2* B1* B1* B2* B1* B2* B1* B2* B1* B2*	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 1/2008 2/2009 11/2009 12/2009	Griffin Galliano Young et al. Smith Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al. Moss	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 89/1.818 124/64 92/140
6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617,818 7,637,203 7,685,920	B1* B1* B2* B2* B1* B2* B1* B2* B2* B2* B2* B2* B2* B2*	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 1/2008 2/2009 11/2009 12/2009 3/2010	Griffin Galliano Young et al. Smith Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al. Moss Paul	89/1.817 114/238 280/737 209/139.1 42/1.14 367/144 89/1.818 124/64 92/140 89/1.817
6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617,818 7,637,203 7,685,920 7,775,148	B1* B1* B2* B2* B1* B2* B1* B2* B2* B2* B2* B2* B1* B2* B2* B2* B2* B2*	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 1/2008 2/2009 11/2009 12/2009 3/2010 8/2010	Griffin Galliano Young et al. Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al. Moss Paul McDermott	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 89/1.818 124/64 92/140 89/1.817 89/1.817
6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617,818 7,637,203 7,685,920 7,775,148 7,845,282	B1* B1* B2* B2* B1* B2* B1* B2* B2* B1* B2* B2* B1* B2* B2* B1* B2* B2* B2* B2* B2* B2* B2* B2* B2* B2	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 1/2008 2/2009 11/2009 12/2009 3/2010 8/2010 2/2011	Griffin Galliano Young et al. Smith Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al. Moss Paul McDermott Sheridan et al.	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 367/144 92/140 92/140 89/1.817 89/8 102/473 92/140
6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617,818 7,637,203 7,685,920 7,775,148 7,845,282 7,954,412 2001/002263	B1* B1* B2* B2* B1* B1* B2* B2* B1* B2* B2* B1* B2* B2* B2* B2* B2* B2* B2* B2* B2* B2	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 2/2009 11/2008 2/2009 12/2009 3/2010 8/2010 12/2010 6/2011 10/2001	Griffin Galliano Young et al. Smith Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al. Moss Paul McDermott Sheridan et al. Jansson Vochimura	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 367/144 92/140 89/1.817 89/8 102/473 89/1.817 
6,979,021 7,182,014 7,267,230 7,313,881 7,317,662 7,484,450 7,617,818 7,637,203 7,685,920 7,775,148 7,845,282 7,954,412 2001/0032638 2002/0096041	B1 * B1 * B1 * B2 * B2 * B1 * B2 * B2 *	6/2004 2/2005 12/2005 2/2007 9/2007 1/2008 2/2009 1/2008 2/2009 12/2009 3/2010 8/2010 8/2010 12/2010 6/2011 10/2001 7/2002	Griffin Galliano Young et al. Smith Smith Gieseke et al. Unsworth et al. Hunn et al. T rchik et al. Moss Paul McDermott Sheridan et al. Jansson Yoshimura Briggs et al.	89/1.817 114/238 280/737 89/16 209/139.1 42/1.14 367/144 367/144 89/1.818 124/64 89/1.817 89/1.817 124/81 89/1.817

2007/0251120      A1*      11/2007      Connell      34/576        2007/0251615      A1*      11/2007      Amtower      149/37        2009/0255432      A1*      10/2009      Zhang et al.      102/307        2010/0078004      A1*      4/2010      Oleynik et al.      124/73        2010/0251694      A1*      10/2010      Hugus et al.      60/253        2010/0282115      A1*      11/2010      Sheridan et al.      102/491	2003/0089435 2004/007123 2004/0074381 2005/0139363 2006/0060692 2006/009645 2006/0096449 2006/0225716 2007/0144506	A1* A1* A1* A1* A1* A1* A1* A1* A1*	5/2003 1/2004 4/2004 6/2005 3/2006 5/2006 5/2006 10/2006 6/2007	Sanderson et al.      149/19.1        Ritchie et al.      89/1.14        Smith      89/16        Thomas      169/30        Yehezkeli et al.      244/3.21        Paul      89/1.817        Williams et al.      89/1.817        Lapointe      124/64        Sun et al.      124/67
2009/0255432      A1*      10/2009      Zhang et al.      102/307        2010/0078004      A1*      4/2010      Oleynik et al.      124/73        2010/0251694      A1*      10/2010      Hugus et al.      60/253        2010/0282115      A1*      11/2010      Sheridan et al.      102/491	2007/0251120 2007/0251615	Al* Al*	11/2007 11/2007	Connell
	2009/0255432 2010/0078004 2010/0251694 2010/0282115	A1* A1* A1* A1*	10/2009 4/2010 10/2010 11/2010	Zhang et al.      102/307        Oleynik et al.      124/73        Hugus et al.      60/253        Sheridan et al.      102/491

#### FOREIGN PATENT DOCUMENTS

2058302 A * 4/1981
2000-130991 A 5/2000
2002316067 A 10/2002
2004274942 A 9/2004
20-0279401 Y1 6/2002
100772493 B1 11/2007
2063572 C1 7/1996
2084260 C1 7/1997
397794 A * 2/1974

#### OTHER PUBLICATIONS

Alfer'ev, K.V. et al., Mechanics of Autonomous Gas-Dynamic Torpedo Motion in Loose Medium, Journal of Mining Science, 2002, pp. 324-328, vol. 38, No. 4.

Borovikov, V.V., Development of a Containment Cavity in a Layer of Free-Flowing Material in Gaseodynamic Outburst from a Subsurface Gas Source, Journal of Mining Science, 1997, pp. 41-46, vol. 33, No. 1.

Borovikov, V.V. et al., Dynamics of a Soil Mass Subjected to a Deep Source of Gaseous Energy, Journal of Mining Science, 1995, pp. 51-55, vol. 31, No. 1.

Alfer'ev, K.V. et al.; The Effect of Rigid Boundaries on the Directionality of an Excavating Explosion; Combustion, Exposion, and Shock Waves; 2001; pp. 613-615: vol. 37, No. 5.

Borovikov, V.V. et al., Analysis of Energy Expenditures of Cold Gas on Ejection, Journal of Mining Science, 1995, pp. 364-365, vol. 31, No. 5.

Borovikov, V.V., Numerical Modeling of Gaseodynamic Processes in the Atmosphere Occurring with Detonation of a Vertical Deep-Hole Charge, Journal of Mining Science, 1995, pp. 427-432, vol. 31, No. 6.

Borovikov, V.V., Evaluation of Intensity of Loading in a Massif of Loose Material in the Zone of Action of an Underground Gaseodynamic Discharge, Journal of Mining Science, 1995, pp. 416-420, vol. 31, No. 6.

Borovikov, V.V., Numerical Modeling of the Magnitude of the Load on a Mass of Free-Flowing Material Subjected to the Action of a Gaseodynamic Source, Journal of Mining Science, 1997, pp. 348-355, vol. 33, No. 4.

Borovikov, V.V., Numerical Studies of Transportation of Granular Material by a Pin-Point Blast Using Models of the Mechanics of Continuous and Granular Media, Journal of Applied Mechanics and Technical Physics, 1998, pp. 1-11, vol. 39, No. 1.

Borovikov, V.V. et al., Gas-Dynamic Method of Decreasing the Force of Penetration of a Solid Into Ground, Journal of Applied Mechanics and Technical Physics, 1999, pp. 531-534, vol. 4, No. 3.

Borovikov, V.V. et al., Efficiency of Pulse Gas-Dynamic Technique of Pneumatic Transportation of Friable Materials, Journal of Mining Science, 1996, pp. 54-57, vol. 32, No. 1.

Borovikov, V.V et al.; The Use of Wave Effects of Pinpoint Underground Explosion; Combustion, Explosion, and Shock Waves; 2000; pp. 414-416; vol. 36, No. 3.

Borovikov V. Numerical investigations of transportation of loose material by directed explosion on the basis of models of solid and loose media mechanics. AMTP.-1998.—No. 1.

Borovikov V, Alferiev K, Lubarski S. Influence of rigid boundaries on directivity of outburst explosion. CESW, v.37, No. 5, 2001.

Borovikov V. Numerical modeling of intensity of loading of loose material body under the influence of the gas dynamical source. JMS.-1997.—No. 4.

Borovikov V. Development of camouflet space in the loose material layer at gas dynamical outburst out of an underground gas source. JMS.-1997.-No. 1.

Borovikov V, Alferiev K, Ebel A. Mechanics of movement of a pulse gas dynamical torpedo in loose medium. JMS.—No. 4, 2002.

Borovikov V, Guskov V, Sokolov A. Utilization of wave effects on directional explosions in ground. CESW, No. 3, 2000.

Borovikov V, Bystrov A. Pulse gas dynamical method of reducing the force of penetration of solid bodies into the ground. AMTP.— 1999.—v.40.—No. 3.

Borovikov V, Ivanov A, Lubarski S, Pivak B. The efficiency of pulsed gas-dynamic method for transportation of granular materials. JMS.—1996.—No. 1.

Borovikov V. Numerical modeling of gas dynamical processes in atmosphere during the explosion of vertical well charge. JMS.— 1995.—No. 6.

Borovikov V. Evaluation of the intensity of loading the loose material body in the influence zone of underground gas dynamical obstruct. JMS.—1995.—No. 6. Borovikov V, Ivanov A, Gorbunkov A, Lubarski S. Analysis of energy consumption of a cool gas for performance of outburst work. JMS.— 1995.—No. 5.

Borovikov V, Ivanov A, Lubarski S. Dynamics of the ground body under the influence of underground gas energy source. JMS.— 1995.—No. 1.

Approximate calculation of throwing a massive body without packing by a two-phase flow Sadin, D.V.1; Sklyar, V.A.1, Fizika Goreniya i Vzryva, v 34, n 3, p. 117-120, May-Jun. 1998.

Throwing of a noncompacted massive body by the two-phase medium flow Sklyar, V.A.1, Fizika Goreniya i Vzryva, v 32, n. 3, p. 119-121, May-Jun. 1996.

Influence of channel recoil on the velocity of throwing of a massive solid body by a two-phase torrent of the bulk density Sklyar, V.A.1, Fizika Goreniya i Vzryva, v 32, n 6, p. 129-133.

International Preliminary Report on Patentability; Dec. 16, 2010; issued in International Patent Application No. PCT/US2009/045936. International Search Report; Jun. 16, 2010; issued in International Patent Application No. PCT/US09/63173.

Written Opinion of the International Searching Authority; Jun. 16, 2010; issued in International Patent Application No. PCT/US09/63173.

\* cited by examiner









![](_page_7_Figure_4.jpeg)

![](_page_8_Figure_4.jpeg)

![](_page_9_Figure_4.jpeg)

![](_page_9_Figure_5.jpeg)

FIG. **13** 

![](_page_9_Figure_7.jpeg)

![](_page_10_Figure_4.jpeg)

![](_page_10_Figure_5.jpeg)

![](_page_10_Figure_6.jpeg)

![](_page_10_Figure_7.jpeg)

![](_page_10_Figure_8.jpeg)

![](_page_11_Figure_4.jpeg)

![](_page_11_Figure_5.jpeg)

![](_page_11_Figure_6.jpeg)

![](_page_11_Figure_7.jpeg)

![](_page_11_Figure_8.jpeg)

![](_page_12_Figure_4.jpeg)

![](_page_12_Figure_5.jpeg)

![](_page_12_Figure_6.jpeg)

![](_page_12_Figure_7.jpeg)

![](_page_12_Figure_8.jpeg)

![](_page_13_Figure_4.jpeg)

![](_page_13_Figure_5.jpeg)

![](_page_13_Figure_6.jpeg)

![](_page_13_Figure_7.jpeg)

![](_page_13_Figure_8.jpeg)

![](_page_14_Figure_4.jpeg)

![](_page_14_Figure_5.jpeg)

![](_page_14_Figure_6.jpeg)

FIG. **28** 

![](_page_14_Figure_8.jpeg)

FIG. **29** 

![](_page_15_Figure_4.jpeg)

![](_page_15_Figure_5.jpeg)

![](_page_15_Figure_6.jpeg)

![](_page_15_Figure_7.jpeg)

![](_page_16_Figure_4.jpeg)

![](_page_16_Figure_5.jpeg)

![](_page_16_Figure_6.jpeg)

![](_page_17_Figure_4.jpeg)

![](_page_17_Figure_5.jpeg)

5

40

45

55

65

# EXPLOSIVE DECOMPRESSION PROPULSION SYSTEM

### CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority from provisional patent application having Ser. No. 61/130,547 and filed Jun. 2, 2008, the entire disclosure of which is incorporated herein by reference.

# BACKGROUND OF THE INVENTION

Currently, projectile systems require combustible fuels which explode to propel an object. Such systems pollute the environment, use non-renewable resources, create dangerous explosions, and are expensive.

There is a need to create a projectile propulsion system.

#### SUMMARY

In accordance with an aspect of the present invention, a projectile propulsion system includes a launch tube, multiphase material, and a membrane. The launch tube has an 25 interior cavity, the multiphase material disposed therein. The launch tube also has an opening to receive the multiphase material. The membrane seals the opening while the multiphase material is disposed in the interior cavity of the launch tube so as to allow the launch tube to be pressurized. 30

In some embodiments, when the membrane is broken, a supersonic wave thrusts the contents of the interior cavity, such as a projectile, outwards with a high velocity and force.

Other aspects and features of the present invention, as defined solely by the claims, will become apparent to those <sup>35</sup> ordinarily skilled in the art upon review of the following non-limited detailed description of the invention in conjunction with the accompanying figures.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a projectile propulsion system in accordance with an embodiment of the present invention.

FIG. **2** is a projectile propulsion system in accordance with another embodiment of the present invention.

FIG. **3** is a projectile propulsion system in accordance with another embodiment of the present invention.

FIG. **4** is a projectile propulsion system in accordance with another embodiment of the present invention.

FIGS. **5**A-B (collectively FIG. **5**) is a multistage projectile 50 propulsion system in accordance with another embodiment of the present invention.

FIG. 6 illustrates a method of operation of the multistage projectile propulsion system of FIG. 5 in accordance with an embodiment of the present invention.

FIG. 7 is a multistage projectile propulsion system in accordance with another embodiment of the present invention.

FIG. **8** is a block schematic diagram of an example of a system for projectile propulsion in accordance with an 60 embodiment of the present invention.

FIG. 9 is a method of operation of a projectile propulsion in accordance with an embodiment of the present invention.

FIGS. **10**A-B illustrates a method of operation of the projectile propulsion system of FIG. **3**.

FIGS. **11**A-C illustrates a method of operation of the projectile propulsion of FIG. **2**.

FIGS. **12-36** illustrate a cross-sectional view of the projectile propulsion system according to various embodiments of the present invention.

# DETAILED DESCRIPTION

Embodiments of the present invention are described below with reference to flowchart illustrations and/or block diagrams of method and apparatus (systems). It will be under-10 stood that each block of the flowchart illustrations and/or block diagrams, and/or combinations of blocks in the flowchart illustrations and/or block diagrams, can be controlled by computer program instructions. These computer program instructions may be provided to a processor of a general 15 purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts 20 specified in the flowchart and/or block diagram block or blocks.

FIG. 1 is a projectile propulsion system 100 in accordance with an embodiment of the present invention. The projectile propulsion system 100 includes a launch tube 102, multiphase material (MPM) 104 and a membrane 106. The launch tube 102 may be any container which is capable of holding material (e.g. MPM 104) and capable of being pressurized. The launch tube 102 has an interior cavity 107 for receiving such material. The launch tube 102 may be of any shape or size. For example, the launch tube 102 may be a cylindrical shape, as shown in FIG. 1. The launch tube 102 may be of any size including a hand-held device or a large aerospace rocket. At least a portion of the launch tube 102 is initially hollow. Any type of materials that make up the body of the launch tube, including metals (e.g. steel, aluminum, etc.), plastic (e.g. PVC) and the like. In one embodiment, the launch tube 102 is a hollow pipe or a plastic tube. The launch tube has at least one opening 108 to receive MPM 104 and/or pressurized air/gas.

The MPM **104** is any material having a mulitphased composite structure. An example of such MPM **104** includes sand. In one embodiment, MPM **104** includes any material which has a multiplicity of elements bonded together such that when such bond is broken energy is released. The MPM **104** has porosity greater than 0 but less or equal to 1. At least a portion or all of the interior cavity **107** of the launch tube **102** is filled with MPM **104**.

The membrane **106** is a device which seals the launch tube **102** by covering the opening **108** of the launch tube **102**. The membrane **106** may be made of any material, including plastic, rigid materials, elastic, or any other material. In one embodiment, the membrane **106** is a material which is allowed to be ripped or compromised in response to a predetermined trigger, such as heat, ignition, sharp object, and the like. In another embodiment, the membrane **106** may be a door or other apparatus which may be removable from the opening **108** of the launch tube **102**. The membrane **106** is secured to the launch tube **102** via any manner, such as glue, fasteners, hinge, friction, cap, and the like, to removably seal the launch tube **102**. In one embodiment, multiple membranes (not shown) may be employed to cover multiple openings (not shown).

FIG. 2 is another projectile propulsion system 200 in accordance with another embodiment of the present invention. FIG. 2 illustrates the projectile propulsion system 100 of FIG. 1 with a projectile 202 inserted in the interior cavity 107 of the launch tube 102. At least a portion of the projectile 202 is surrounded by MPM **104**. For example, as illustrated, the projectile **202** is completely surrounded by MPM **104**.

FIG. **3** is a projectile propulsion system **300** in accordance with another embodiment of the present invention. FIG. **3** illustrates the projectile propulsion system **100** of FIG. **1** with **5** a launch tube **302** having at least one characteristic of a rocket. For example, as illustrated, the launch tube **302** has an aerodynamic shape (e.g. pointed front **304**) and fins **306** to direct the launch tube. It should be noted that no projectile in located in the launch tube **302** through space.

FIG. 4 is a multiphase projectile propulsion system 400 in accordance with another embodiment of the present invention. FIG. 2 illustrates the projectile propulsion system 100 of FIG. 1 with a projectile 404 inserted in the interior cavity 107 of the launch tube 102. The projectile 404 is another projectile 15 propulsion system similar to the projectile propulsion system of FIG. 2. Both the interior cavity 102 of the projection propulsion system 400 and the interior cavity 406 of the imbedded projectile propulsion system 404 include MPM 104.

FIGS. 5A-B (collectively FIG. 5) is a multistage projectile propulsion system 500 in accordance with another embodiment of the present invention. FIG. 5A illustrates a plurality of active propulsion systems 502, 504, 506, 508, 510, 512, and 514, each similar to the propulsion system 300 of FIG. 3. 25 Specifically, as illustrated in FIG. 5B, seven projectile propulsion systems 502, 504, 506, 508, 510, 512, and 514 are attached together to form a single multistage projectile propulsion system 500. Three of the projectile propulsion systems 502, 504, 506 of the multistage projectile propulsion 30 system are paired together with three other projectile propulsion systems 508, 512, 514, respectively. The center projectile propulsion system 510 is not paired in the exemplary illustration.

FIG. 6 illustrates a method 600 of operation of the multi- 35 stage projectile propulsion system 500 of FIG. 5 in accordance with an embodiment of the present invention. In the first stage 602 of the multistage projectile propulsion system 600, the first pair of projectile propulsion systems 502, 508 is activated. After the first pair 502, 508 is activated, the second 40 pair of projectile propulsion systems 506, 514 is activated in a second stage 604. Thereafter, for a third stage 606, the third pair 504, 512 of projectile propulsion systems is activated. For the last stage 608, the center projectile propulsion system **510** is activated. It should be understood that any of the above 45 activations 602-608 of the projectile propulsion systems of the multistage projectile propulsion system 600 may be activated in different orders and/or simultaneously with any other stage(s) 602-608. Additionally, any number of stages may be included in the multistage projectile propulsion system. 50

FIG. 7 is another multistage projectile propulsion system 700 in accordance with another embodiment of the present invention. FIG. 7 includes a double multistage projectile propulsion system 703, which includes a thrust projectile propulsion system 701 attached to a multistage projectile pro- 55 pulsion system 705. The thrust projectile propulsion system 704 is similar to the projectile propulsion system 100 of FIG. 1 and includes a MPM 714, launch tube 712, a membrane 716, and an attachment means 710, such as adhesive, releasably fasteners, etc., to attach to the multistage projectile pro- 60 pulsion system 705. The multistage projectile propulsion system 705 is similar to the multistage projectile propulsion system 500 of FIG. 5 and each projectile propulsion system 750-758 of the multistage projectile propulsion system 705 includes MPM 704, launch tube 702, and a membrane 706. 65 The double multistage projectile propulsion system 703 is located in an interior cavity 760 of a launching projectile

4

propulsion system 762, which is similar to the projectile propulsion system of FIG. 1. The launching projectile propulsion system 762 includes MPM 104, launch tube 102, and a membrane **106**. To launch the double multistage projectile propulsion system 703 of FIG. 7 the launching projectile propulsion system 762 is first activated. After the double multistage projectile propulsion system 703 is launched a predetermined time or distance from the launching projectile propulsion system 762, the thrust projectile propulsion system 701 is activated. After the thrust projectile propulsion system 701 is activated for a predetermined time, the multistage projectile propulsion system 705 is activated, similar to that described above with regard to FIG. 6. The description of how to operate or activate each projectile propulsion system 762, 701, 750-758 is described below with reference to FIG. 9.

FIG. 8 is a block schematic diagram of an example of a system 800 for projectile propulsion in accordance with an embodiment of the present invention. The system 800 20 includes at least one projectile propulsion system 802, as previously described with respect to FIGS. 1-7. Also, the system 800 may include one or more input systems 804, such as a system to pressurize the projectile propulsion system 802 with air, gas and the like. The input system 804 may be connected to any portion of the projectile propulsion system 802, including any opening or valve. Additionally, the system 800 may include an activation system 806, which releases the membrane to allow a sudden equalization of pressure between the interior cavity and the exterior of the projectile propulsion system 802. The system 800 may further include a system 808 to capture outward forces released from the projectile propulsion system 802. For example, the capture system 808 may capture MPM expelled from the interior cavity of the projectile propulsion system 802.

FIG. 9 is a method 900 of operation of any projectile propulsion system in accordance with an embodiment of the present invention. In block 902, a launch tube is provided. As previously discussed, the launch tube may be a hollow container capable of receiving MPM and capable of being pressurized. In block 904, the launch tube is filled with material, such as MPM, projectiles, other projectile propulsion systems, or any other material and/or device. In block 906, the launch tube is sealed with a membrane so as to form an airtight seal. In block 908, the launch tube is pressurized by adding air and/or gas to the launch tube to achieve a predetermined pressure in the cavity. In block 910, the pressure of the launch tube is released by, for example, breaking the membrane, opening a door on the launch tube, igniting gas/ fuel in the launch tube, heating the launch tube and/or membrane, and any other way to allow the launch tube to release pressure. By equalizing the pressure of the exterior of the launch tube with the interior cavity of the launch tube, a supersonic wave travels down the longitudinal length in the interior cavity of the launch tube and then travels back up the launch tube toward the opening of the launch tube pushing out any projectile and at least some MPM therein. Additionally, energy from the MPM may be released contributing to the supersonic wave.

FIGS. 10A-B visually illustrates an exemplary method of operation of the projectile propulsion system 300 of FIG. 3. FIG. 10A illustrates the projectile propulsion system 300 of FIG. 3 after pressurization. FIG. 10B illustrates the projectile propulsion system 300 immediately after the membrane 106 is broken, resulting in MPM 104 thrust in a first direction and the launch tube propelled in an opposite direction. As shown, the MPM 104 is released from the interior cavity of the launch tube 302.

FIGS. **11**A-C illustrates an exemplary method of operation of the projectile propulsion system **200** of FIG. **2**. FIG. **11**A illustrates the projectile propulsion system **200** of FIG. **2** when the membrane **106** of projectile propulsion system **200** is first broken. As shown, a supersonic wave **1100** travels 5 down the longitudinal length of the launch tube **102** toward the end **1102** of the launch tube **102**. After the supersonic wave **1100** reaches the end **1102** of the launch tube **102**, the supersonic wave **1100** travels back toward the opening **1104** of the launch tube **102** propelling the projectile **202** of the 10 projectile propulsion system **200**, as shown in FIG. **11B**. MPM **104** is shown as being expelled out of the launch tube **102** along with the projectile **202**. As illustrated in FIG. **11**C, the projectile **202** is forced completely out of the launch tube **102** with a tremendous amount of force and velocity. **15** 

Other embodiments of the projectile propulsion system are illustrated in FIGS. 12-36. These Figures include multiphase material 120, a launch tube 130, compressed gas 140 in porous spaces of the multiphase material, a membrane 150, and a projectile 160. FIG. 12 illustrates a cross-section of the 20 apparatus for launching projectile(s). FIGS. 12-14 illustrates the system having a gas inlet 110. FIG. 14 illustrates the projectile can be hollow. FIG. 15 illustrates the outer surface of the projectile having ridges to achieve increased surface friction force and range. FIG. 16 illustrates the projectile 25 being located inside an outer body shell that is covered with circular ridges to achieve increased surface friction force and decreased aerodynamic resistance forces during the time of flight. FIG. 17 illustrates the inner surface of launch tube has circular ridges to achieve decreased recoil. FIG. 18 illustrates 30 the launch tube having multiple passive projectiles. FIGS. 19-21 illustrate various objects may be attached to the projectiles, such as a net, rope or chain, respectively. FIGS. 22-23 illustrate the projectile being guided inside the launch tube by linear longitudinal ridges or spiral ridges, respectively, along 35 the longitudinal axis of the launch tube. FIGS. 24-26 illustrate the launch tube having several gas inlets to pressurize the launch tube. FIG. 25 illustrates having a membrane to partially or non-hermetically seal the launch tube. FIG. 26 illustrates the launch tube having no membrane sealing the launch 40 tube. FIG. 27 illustrates inserting chemicals or chemical charges into the interior of the launch tube to cause chemical reactions within the launch tube. FIGS. 28-31 illustrate the launch tube being active, which means that the launch tube itself becomes a projectile upon activation or breaking of the 45 membrane. FIG. 29 illustrates a gas inlet located on the membrane. FIG. 30 illustrates separating plates within the launch tube for preventing motion of the non-cohesive loose granular multiphase material inside the interior of the launch tube under the influence of inertial forces. FIG. 31 illustrates aero- 50 dynamic control surfaces on the launch tube's outer surface. FIG. 32 illustrates an active projectile with anchoring foldable or fixed hooks attached to the outer surface of the projectile. FIG. 33 illustrates an active projectile located inside the launch tube, where the active projectile has with a hose 55 inside a chamber of the active projectile. FIG. 34 illustrates a flexible cord or rope being fixed to one end of the active projectile inside the launch tube and a movable weight, charge, an anchor or another payload attached to the other end of the active projectile. FIG. 35 illustrates an active projectile 60 and compressed gas being produced by a chemical charge which is located inside the interior of the active projectile. FIG. 36 illustrates several active projectiles which are located inside a launch tube. It should be understood that other embodiments may also be employed. 65

The flowcharts and block diagrams in the Figures illustrate the architecture, functionality, and operation of possible 6

implementations of systems and methods according to various embodiments of the present invention. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable steps for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the block may occur out of the order noted in the Figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems which perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/ or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad invention, and that this invention not be limited to the specific constructions and arrangements shown and described, since various other changes, combinations, omissions, modifications and substitutions, in addition to those set forth in the above paragraphs, are possible. Those skilled in the art will appreciate that various adaptations and modifications of the just described embodiments can be configured without departing from the scope and spirit of the invention. Therefore, it is to be understood that, within the scope of the appended claims, the invention may be practiced other than as specifically described herein

What is claimed is:

1. A method for propulsion, comprising:

- filling an interior cavity of a tube with a multiphase material, wherein the tube comprises sidewalls, a back wall and an opening, wherein the back wall is opposing the opening, and wherein the multiphase material comprises a multiphased composite structure comprising a multiplicity of elements together;
- disposing a projectile into the interior cavity of the tube such that the projectile is directly surrounded by the multi-phase material;
- sealing the opening of the tube with a membrane while the multi-phase material and projectile are disposed in the interior cavity of the tube;
- pressurizing the sealed tube with a gas while the tube is sealed and prior to launching the projectile; and
- prior to launching the projectile, breaking the membrane thereby equalizing the pressure from the interior cavity with pressure on the exterior of the tube and also thereby resulting in a first shock wave and a second shock wave, the first shock wave emanating away from the projectile and a second shock wave traveling down the tube and reflecting from the back wall of the tube to facilitate pushing propelling the projectile out of the tube.

10

35

2. The method of claim 1, wherein the gas comprises air.

3. The method of claim 1, wherein, in response to the breaking of the membrane, the shockwave travels through the multiphased material, thereby breaking up the multiphased material proximate the back wall and causing the multiphased material to be propelled against the projectile so that the projectile is pushed out of the tube.

4. The method of claim 1, wherein the multiphase material comprises sand.

5. The method of claim 1, wherein the projectile comprises at least one propulsion system, wherein the propulsion system comprises a tube, multiphase material, another projectile and a removable barrier.

6. The method of claim 1, wherein the membrane comprises a removable pressure barrier, and wherein the tube is pressurized to 35,000,000 Pa prior to breaking the removable barrier.

7. A method comprising:

- providing a projectile propulsion system comprising a tube 20 comprising an interior cavity and an opening;
- disposing multi-phase material in the interior cavity, wherein the multiphase material comprises a multiplicity of elements together;
- disposing a projectile into the interior cavity of the tube 25 such that the projectile is surrounded by the multi-phase material:
- sealing the opening of the tube with a removable barrier while the multi-phase material and projectile are disposed in the interior cavity of the tube;
- pressurizing the sealed tube with a gas while the tube is sealed and prior to launching the projectile; and
- prior to launching the projectile and after pressuring the sealed tube, removing the removable barrier to allow equalization of pressure from outside of the launch tube and the interior cavity of the launch tube so that when the removable barrier is removed, the projectile is launched from the tube.

8. The method of claim 7, wherein the tube comprises sidewalls, a back wall and an opening, wherein the back wall is opposing the opening, and wherein the multiphase material comprises a multiphased composite structure comprising a multiplicity of elements bonded together.

9. The method of claim 8, wherein the gas comprises air.

10. The method of claim 7, wherein prior to launching the projectile, removing the barrier thereby equalizing the pressure from the interior cavity with pressure on the exterior of 8

the tube and also thereby resulting in a first shock wave and a second shock wave, the first shock wave emanating away from the projectile and a second shock wave traveling down the tube and reflecting from the back wall of the tube to facilitate pushing and propelling the projectile out of the tube.

11. The method of claim 7, wherein the removing the removable barrier comprises breaking a membrane, and wherein the breaking of the membrane comprises heating the membrane.

12. A method of manufacturing a projectile propulsion system, comprising: providing a tube comprising an interior cavity and an opening; disposing multiphase material and a projectile in the interior cavity, wherein the multiphase material comprises sand; pressurizing the interior cavity to 35,000, 000 Pa prior to breaking a membrane or removing a barrier and prior launching of the projectile; and sealing the opening so that the interior cavity stays pressurized so that when the membrane is broken or barrier is removed, the multiphase material and a shock wave launches the projectile from the tube.

13. A system of a multiphase projectile propulsion system, comprising: a tube comprising an opening and an interior cavity defined by sidewalls and a back wall, wherein the back wall is opposing the opening; multi-phase material disposed in the interior cavity, wherein the multiphase material comprises a multiphased composite structure comprising a multiplicity of elements together; a projectile disposed into the interior cavity of the tube such that the projectile is directly surrounded by the multi-phase material, wherein the projectile comprises at least one propulsion system, wherein the propulsion system comprises a tube, multiphase material, another projectile and a removable barrier; and a pressure barrier or membrane configured to seal the opening while the multi-phase material and projectile are disposed in the interior cavity of the tube, wherein membrane allow pressurization of the tube with a gas while the tube is sealed and prior to launching the projectile, and wherein prior to launching the projectile, breaking the membrane or removing the pressure barrier equalizes the pressure from the interior cavity with pressure on the exterior of the tube and also thereby resulting in a first shock wave and a second shock wave, the first shock wave emanating away from the projectile and a second shock wave traveling down the tube and reflecting from the back wall of the tube to facilitate pushing propelling the projectile 45 out of the tube.